# **OW Ebony Black Restorer**

Description	Ebony fingerboards are highly valued in musical instruments for their hardness, durability, and rich, dark aesthetics. However, sometimes, ebony can have lighter streaks or spots that may detract from its appearance. OW has developed the product <b>Ebony Black Restorer</b> , allowing luthiers to darken these ebony pieces to enhance their appearance and provide a more uniform colour.
	<b>Ebony Black Restorer</b> is not a simple water-based dye. This product combines dyes and micronized pigments, providing more effective and long-lasting colouration. It has good penetration and provides a uniform colour.
Composition	It is a water-based product that is odourless and non-flammable, making it ideal for indoor work as it avoids strong odours and the health risks associated with traditional solvents.
	Water-based product. Contains micro pigments highly resistant to light. Free from harsh solvents. Safe, non-flammable, non-irritating. No health or environmental risks, in compliance with EU Regulation No. 1272/2008
Properties	(CLP).
	Low-odor liquid. Colour: black. Water-based product. Non-flammable. Quick drying.
Application	
	Instructions: Thoroughly clean the fingerboard to remove any dirt, oil, or residue.
	Shake the contents of the container until the product is perfectly homogenized.
	Use a clean cloth to apply the dye evenly. Soak the cloth with the product and spread it along the entire piece to be dyed. The product spreads easily. Remove any excess product with a soft cloth to avoid buildup.
	The product dries quickly (5 minutes). If a second coat is desired, wait 20-30 minutes.
	Once the product is completely dry, rub the surface with a clean cloth to remove any remaining product.
	To protect the colour and ensure proper durability, it is necessary to apply a suitable oil for wood care afterwards, such as <b>OW Oil for Ebony</b> . It can be used 6 to 8 hours later. Add a few drops to a clean cloth and spread it evenly over the entire surface, avoiding buildup or excess product. Wait 24 hours if a second coat is desired.



#### Technical Data v.01/2024

# OldWood

## Storage

**Storage:** The product can be stored for over a year in its original container, tightly closed and protected from the elements (indoors and at temperatures between 5 and 35°C).

Keep the container tightly closed and in a cool place, and avoid direct sunlight. Avoid heat, radiation, static electricity, and contact with food. Under these conditions, the product is stable for over a year.

### Security



According to Regulation No. 1272/2008 (CLP), this product is not classified as a hazardous substance or mixture.

Avoid contact with eyes and skin. In case of contact, rinse immediately with water. Do not ingest. Keep out of reach of children.

According to available data, it is not considered hazardous to the environment. Its components are readily biodegradable.

It is recommended to use protective gloves against minor risks and panoramic goggles against splashes and projections.

All information related herein is provided to the best of our knowledge and understanding and should not be considered a guarantee. The recipient must conduct tests to determine the suitability of the information provided.

