OW Thinner

A pure solvent for your varnish

Description

The OW Thinner is a high-purity, suitable solvent substitute for turpentine and other similar products. It can be used when formulating oil varnishes or cleaning tools.

It is non-flammable and free of aromatic compounds, offering good performance, minimal odour, and reduced risk in your work area.

Composition

Hydrocarbons, < 2% aromatic compounds.

Properties

Aspect: Transparent and clear liquid
Free of aromatic hydrocarbons
Flashpoint > 61 ºC.
Density (20C): 0.76 g/cc
Solubility: insoluble in water

Because of its high flash point, this product is less dangerous than regular solvents (turpentine, white spirit, mineral spirits...) and without the regular lousy odour.

Since it is pure, it evaporates completely and does not leave a residue, which is essential because it does not affect the tonalities or drying time. It also does not deteriorate during storage.

OW thinner evaporates a bit slower than turpentine or other solvents. Therefore, it keeps the coating open longer, allowing a better application and an excellent varnish levelling over the instrument surface.

Application

Whether you decide to dilute the varnish or not is a very personal choice, and the dilution and later application techniques will depend entirely on your preferences and expertise.

OldWood Colours & Varnishes
Plaza Castilla, 3 – **CP.** 28046 Madrid – Spain
T. + 34 914 118 992**www.oldwood1700.com**

Storage

Store it tightly closed and in a cool, dry location, avoiding exposure to direct light or outdoor elements. Avoid heat, radiation, and static electricity. Under these conditions, the Hide Glue Collagen is stable for over two years.

Security

According to Regulation No 1272/2008 (CLP), this product is classified as:

Asp. Tox. 1: Aspiration hazard, Category 1, H 304.
EU H066: Repeated exposure may cause skin dryness or cracking.

Protective gloves are recommended against minor hazards, and panoramic goggles are recommended against splashes and/or projections to prevent eye or skin contact.

Respiratory protection: Protection equipment will be necessary if a mist forms or the occupational exposure limits are exceeded.

Packaging

PET bottles of 250 ml.

All information related herein is provided to the best of our knowledge and understanding and should not be considered a guarantee. The recipient must conduct tests to determine the suitability of the information provided.

OldWood Colours & Varnishes
Plaza Castilla, 3 – **CP.** 28046 Madrid – Spain
T. + 34 914 118 992**www.oldwood1700.com**